5138/USSN 09/581,565 Group Art Unit 2834

Brt.

comparison to said substrate, wherein the capacitor is conductively connected in series to said component such that temperature data from said component are transmitted over a two-pole supply lead that is used to supply said first electrode and said second electrode.

- -- 14. (New) A piezoelectric ultrasound transmitter according to claim 13, wherein said first electrode has a nose, which provides on said first surface a connecting pad via which said component is conductively connected to said first electrode.
- -- 15. (New) A piezoelectric ultrasound transmitter according to claim 14, wherein said second electrode has a nose, which extends over the rim of said substrate and provides on said first surface a connecting pad via which said component is conductively connected to said second electrode.
- -- 16. (New) A piezoelectric ultrasound transmitter comprising a substrate made of a piezoelectric material provided with a first electrode on a first surface and a second electrode on a second surface opposite said first surface, said first electrode and said second electrode forming a capacitor, said first surface having an electrode-free rim surface on which is disposed a component having temperature-dependent behavior and a high impedance in comparison to said substrate, wherein the capacitor is

5138/USSN 09/581,565 Group Art Unit 2834

By.

conductively connected in parallel to said component such that temperature data from said component are transmitted over a two-pole supply lead that is used to supply said first electrode and said second electrode.

- -- 17. (New) A piezoelectric ultrasound transmitter according to claim 13 or 16, wherein said substrate is made of a piezoceramic.
- -- 18. (New) A piezoelectric ultrasound transmitter according to claim 16, wherein said first electrode has a nose, which provides on said first surface a connecting pad via which said component is conductively connected to said first electrode.
- -- 19. (New) A piezoelectric ultrasound transmitter according to claim 18, wherein said second electrode has a nose, which extends over the rim of said substrate and provides on said first surface a connecting pad via which said component is conductively connected to said second electrode.
- -- 20. (New) A piezoelectric ultrasound transmitter according to claim 14, 15, 18 or 19, wherein said component is a PTC resistor.
- -- 21. (New) A piezoelectric ultrasound transmitter according to claim 14, 15, 18 or 19, wherein said component is a NTC resistor.